JEPSON POWER® GERMANY

Leading Through Innovation

Management System ISO 9001:2015

TÜVRheinland ZERTIFIZIERT

www.tuv.com ID 9105068261

Premium Super Dry Cutter 9435 - The Reference

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, **stainless steel**, aluminium, plastic and composite materials
- No need of lubricant and manual deburring
- **Exclusive blade stabilising system** reduces vibrations
- High torque motor for continuous operation
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Fitted with a Ø 14"/90T HM saw blade
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	18 amps
Voltage	115V/50Hz
No load speed	1.400 rpm
Net weight	56 lbs
Blade size	14"

Maximum cutting capacities in **inch**

	90° Cutting	45° Miter Cut
Round	5.511"	4.724"
Square	4.921 x 4.921 "	3.149 " x 3.149 "
Rectangular	4.133 " x 6.102 "	2.952 " x 3.937 "



600526T3



600546



609910

Premium Super Dry Cutter 9435	Ref.
with 14"/90T Saw blade 115V	600560UST3
Stand for PSDC 9435	600526T3
Thinfix- clamp for open profiles	600546
Eccentric clamping system	609910

HM Saw blades	Ref.
14"/90T for stainless steel-food	600570NSF
14"/90T for thin steel and stainless steel	600570S
14"/72T for medium steel and stainless steel	600580S
14"/60T for thick steel and stainless steel	600590
14"/60T for cast iron	600591S
14"/66T for mild steel	600595S
14"/96T for aluminum	600594