

NO MORE CHIPPED TEETH

LBS impact resistant saw blades by DRYTECH[®]

Ideal for cutting **metal grids** and **grates**, trapezoidal sheets, metal profiles, conduits, shutter pipes and much more.

With **0.4"** up to **.59"** LBS-blades are **much thinner** than conventional saw blades. Therefore sawing with LBS-saw blades saves material and time!



The brand names used by the respective companies are subject to general trademark, trademark or patent protection.

Range of LBS-saw blades							
Ø	Kerf	Blade body width	Bore	Teeth	max. load speed	Ref.	for machine
5 3/8"	.04"	.03"	.079"	30	4500 rpm	72213730	Bosch, Milwaukee, etc.
6 1/2"	.05"	.037"	.079"	34	4200 rpm	72215034	Milwaukee
6 1/2"	.05"	.037"	.062"	40	4200 rpm	72216540M	Metabo
7"	.05"	.037"	.079"	48	4000 rpm	72218048	Flex, Hitachi, Makita, Rexon, etc.
7 1/2"	.05"	.037"	.079"	48	4000 rpm	72219248	JEPSON Power HDC 8219
8"	.05"	.037"	1"/1.181"	48	3800 rpm	72220348	AEG, Bosch, JEPSON Power etc.
9"	.055"	.047"	1"	60	3000 rpm	72223060	JEPSON Power HDC 8230N
10"	.059"	.047"	1"	66	2200 rpm	72225566	JEPSON Power DMC 9410ND