

## Super Hand Dry Cutter 8320

with Ø 12 5/8"/84T HM saw blade:

- Ideal for cutting sandwich panels, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to cutting depth of 4 3/4" on guide rail
- Dry cutting without lubricant, instead of a chainsaw
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:  
green: ok | orange: warning | red: over load
- Lightweight magnesium: 18,5 lbs



### Cutting guide 4ft 7" with quick fixation

- Ideal for clean and straight cutting of sandwich panels
- Delivered with 2 C-clamps

### Specifications

|               |           |
|---------------|-----------|
| Power input   | 15 amps   |
| Voltage       | 115V/60Hz |
| No load speed | 1.700 rpm |
| Net weight    | 18,5 lbs  |
| Blade size    | 12 5/8"   |
| Cable         | 16 ft 5"  |

### HM saw blades

### Ref.

|  |           |
|--|-----------|
| Ø 12 5/8"/ 84T CT Saw blade                                      | 608276    |
| Ø 12 5/8"/ 72T CT Saw blade                                      | 608278    |
| Ø 12 5/8" CT Saw blade for stainless steel - food & construction | 608276NSF |

### Accessories (optional)

|  |           |
|--|-----------|
| Cutting guide rail 4ft 7"              | 608275D   |
| Cutting guide rail 4ft 7" + 2 C-Clamps | 608275SET |
| Heavy Duty Professional Blow Case      | 60827BOX  |

### Super Hand Dry Cutter

### Ref.

|   |                   |
|---|-------------------|
| Super Hand Dry Cutter 8320 - delivered with Ø 12 5/8"/84T Saw blade | 608270 / 608270 U |
|---|-------------------|



608270SET



60827BOX