JEPSON POWER® GERMANY

Leading Through Innovation

TÜVRheinland ZERTIFIZIERT
Management System ISO 9001:2015
www.tuv.com ID 9105068261

Hand Dry Cutter 8230N - the mobile

with Ø 9“/48T HM saw blade:

DRY-CUT TECHNOLOGY
Dry cutting without lubricant

- Ideal for cutting metal sheets, sandwich panels, trapezoidal sheets, steel pipes & profiles, nonferrous metals and composite materials
- Optional with impact resistant LBS-blade for grids & grates
- By default fitted with a Ø 9“/48T resharpenable HM-saw blade for highest cutting lifes at a high cutting quality
- Strong and light construction: 15,7 lbs
- Chip collector for clean work
- Maximum cutting depth **3.228“ / 2.204“** bevel cut
- Cutting up to a thickness of **.393“** at 90°



Specifications	
Motor output	17 amps
Voltage	115V/60Hz
No load speed	2.600 tpm
Net weight	15,7 lbs
Blade size	9“
Cable	16 ft. 5“

Maximum cutting capacities in mm

	90° Cutting	45° Bevel cut
Cutting depth	3.228“	2.204“
Square	3.228“ x .196“	2.204“ x .157“
Round	3.228“ x .196“	2.204“ x .157“
Plane	.393“	.314“



72223060



608284

Description: HDC 8230N +	Ref.
9“/48T for inox	608280IUS

Saw Blades	Ref.
9“/48T standard for steel	72123048
9“/48T for steel / inox	72123048Y
9“/48T - for stainless steel food & construction	72123048NSF
9“/60T for aluminum	72123060
9“/68T for thin walled material	72123068
9“/84T for thin sheet metal	72123084
9“/60T LBS-blade shock resistant	72223060

Accessoires	Ref.
Guide rail with integrated clamping system	608284