

## Premium Super Dry Cutter 9435 - The Reference

with Ø 14"/90T HM saw blade:



### DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, **stainless steel**, aluminium, plastic and composite materials
- **Exclusive blade stabilising system** reduces vibrations
- High torque motor for continuous operation
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Optional stand for a complete and save work place
- CE approved operating system

### Specifications

Power input	18 amps
Voltage	115V/50Hz
No load speed	1.400 rpm
Net weight	56 lbs
Blade size	14"

### Maximum cutting capacities in inch

	90° Cutting	45° Miter Cut
Round	5.511"	4.724"
Square	4.921 x 4.921 "	3.149" x 3.149"
Rectangular	4.133" x 6.102"	2.952" x 3.937"



600526T3



600546



609910



### Premium Super Dry Cutter 9435

**Ref.**

with 14"/90T Saw blade 115V 600560UST3

### HM Saw blades

**Ref.**

14"/90T for stainless steel-food 600570NSF

14"/120T for very thin steel and stainless steel 600512

14"/90T for thin steel and stainless steel 600570S

14"/72T for medium steel and stainless steel 600580S

14"/60T for thick steel and stainless steel 600590

14"/60T for cast iron 600591S

14"/66T for mild steel 600595S

14"/96T for aluminum 600594

### Accessories (optional)

Stand for PSDC 9435 600526T3

Thinfix- clamp for open profiles 600546

Eccentric clamping system 609910