

Premium Super Dry Cutter 9435 - The Reference

with Ø 14"/90T HM saw blade:

DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, stainless steel, aluminium, plastic and composite materials
- **Exclusive blade stabilising system** reduces vibrations
- High torque motor for continuous operation
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	21 amps
Voltage	115V/50Hz
No load speed	1.400 rpm
Net weight	56 lbs
Blade size	14"

Maximum cutting capacities in inch

	90° Cutting	45° Miter Cut
Round	5.511"	4.724"
Square	4.921 x 4.921"	3.149" x 3.149"
Rectangular	4.133" x 6.102"	2.952" x 3.937"



600526T3



600546



609910

Premium Super Dry Cutter 9435	Ref.
with 14"/90T Saw blade 115V	600560UST3

HM Saw blades	Ref.
14"/90T for stainless steel-food	600570NSF

14"/120T for very thin steel and stainless steel	600512
--	--------

14"/90T for thin steel and stainless steel	600570S
--	---------

14"/72T for medium steel and stainless steel	600580S
--	---------

14"/60T for thick steel and stainless steel	600590
---	--------

14"/60T for cast iron	600591S
-----------------------	---------

14"/66T for mild steel	600595S
------------------------	---------

14"/96T for aluminum	600594
----------------------	--------

Accessories (optional)

Stand for PSDC 9435	600526T3
---------------------	----------

Thinfix- clamp for open profiles	600546
----------------------------------	--------

Eccentric clamping system	609910
---------------------------	--------