

Super Hand Dry Cutter 8320

with Ø 12 5/8" / 84T HM saw blade:



DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Ideal for cutting **sandwich panels**, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to **cutting depth of 4 3/4" on guide rail**
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:
green: ok | **orange: warning** | **red: over load**
- **Lightweight magnesium: 18,5 lbs**



Cutting guide 4ft 7" with quick fixation

- Ideal for clean and straight cutting of sandwich panels
- Delivered with 2 C-clamps

Specifications

Power input	16 amps
Voltage	115V/60Hz
No load speed	1.700 rpm
Net weight	18,5 lbs
Blade size	12 5/8"
Cable	16 ft 5"

HM saw blades

Ref.

Ø 12 5/8" / 84T CT Saw blade	608276
Ø 12 5/8" / 72T CT Saw blade	608278
Ø 12 5/8" CT Saw blade for stainless steel - food & construction	608276NSF

Accessories (optional)

Cutting guide rail 4ft 7"	608275D
Cutting guide rail 4ft 7" + 2 C-Clamps	608275SET
Heavy Duty Professional Blow Case	60827BOX

Super Hand Dry Cutter

Ref.

Super Hand Dry Cutter 8320 - delivered with Ø 12 5/8" / 84T Saw blade	608270 / 608270 U
---	-------------------



608270SET



60827BOX