

HAND DRY CUTTER 8203E



SPECIFICATIONS

Eco friendly	✓
# Reference	608295ENA
⚡ Voltage	18 V
⚙ Bore Ø	1" / 0.79"
⚙ No load speed	3.500 min ⁻¹
⚖ Net weight (w/o blade & battery)	12 lbs
⚙ Blade size Ø	8"

MAXIMUM CUTTING CAPACITIES [inch]

○ Round 90° 45°	2 5/8 x 1/4 1 5/8 x 1/4
□ Square 90° 45°	2 5/8 ² x 1/4 1 5/8 ² x 3/16 (bevel cut)
▭ Rectangular 90° 45°	2 5/8 x 1/4 1 5/8 x 3/16 (bevel cut)
∧ Angle 90° 45°	2 5/8 ² x 1/4 1 5/8 ² x 3/16 (bevel cut)
— Sheet 90° 45°	3/8 5/16 (bevel cut)
⚙ Cutting depth 90° 45°	2 5/8 1 5/8 (bevel cut)
⚙ Bevel cut	0-45°

Hand Dry Cutter 8203E

with Ø 8"/48T carbide tipped saw blade
„LBS impact resistant“:

- No need for lubrication thanks to our **DRY CUT TECHNOLOGY**
- Ideal for cutting metal sheets, gratings, sandwich panels, trapezoidal sheets, steel pipes & profiles, nonferrous metals and composite materials
- Equipped with a Ø 8"/48T carbide tipped „LBS impact resistant“ saw blade for the highest cutting life and quality
- Chip collector for clean work
- With 2 high performance 18V LiHD 5,5A batteries
- Air-cooled LiHD high speed loading station

SCOPE OF DELIVERY

Ø 8"/48T carbide tipped saw blade „LBS impact resistant“	72220348
2x High performance 18V LiHD 5,5A battery	2x 608295EB
Air-cooled LiHD high speed loading station 110V	608295EC1
2x Guide rail adapter	608275A

OPTIONAL

Ø 8"/54T carbide tipped saw blade for stainless steel	72120354I
Guide rail 4ft 7" / 1.400mm with 2x C-clamp	608275SET