



HAND DRY CUTTER 8230N

THE AGILE

- By default fitted with a Ø 9"/230/48T resharpenable saw blade for highest cutting lives at a high cutting quality
- Strong and light construction, only 16 lbs/7,1 kg
- Chip collector for clean work
- No need of lubrication
- Maximum cutting depth 3,22" / 2,20 bevel cut and thickness 0,40"



CHIP COLLECTOR



Ideal for gratings with LBS saw blade shock-resistant



Saws sheet metal up to 10 mm and sandwich panels and profiles with a cutting depth of up to 82 mm



Depth adjustment with scaling



Chip compartment



45° bevel cut

Power input	Voltage	No load speed	Net weight	Blade size	Bore	Cable length
15 amps	115V / 60Hz	2.600 rpm	16 lbs/7,1 kg	Ø 9"/230 mm	Ø 1"/25,4	5 m

Hand Dry Cutter 8230N + Case	Reference
with Ø 9"/48T saw blade for stainless steel	608280IUS
with 9"/48T saw blade for stainless steel + adjustable cutting guide rail with integrated clamping system	608280IUSET

Max. cutting capacities	90°		45° (bevel cut)
Round	3,228" x 0,196" 82 x 6 mm	2,204" x 0,157" 56 x 6 mm	
Square	3,228" x 0,196" 82 x 82 x 6 mm	2,204" x 0,157" 56 x 56 x 4 mm	
Angle	3,228" x 0,393" 82 x 82 x 6 mm	2,204" x 0,314" 56 x 56 x 4 mm	
Plane	0,393"/10 mm	0,314"/8 mm	
Cutting depth	3,228"/82 mm	2,204"/56 mm	

Saw blades	Reference
Ø 9"/48T	72123048
Ø 9"/48T steel and stainless steel	72123048I
Ø 9"/48T steel and stainless steel - coated food and construction	72123048NSF
Ø 9"/60T - aluminum	72123060
Ø 9"/68T- thin walled material	72123068
Ø 9"/84T - thin sheets	72123084
Ø 9"/60T - LBS metal grids	72223060

Accessories	Reference
Cutting guide rail with integrated clamping system (24" - 47" / 600 - 1200 mm)	608284