



# HAND DRY CUTTER 8230N

## THE AGILE

- By default fitted with a Ø 9"/230/48T resharpenable saw blade for highest cutting lifes at a high cutting quality
- Strong and light construction, only 16 lbs/7,1 kg
- Chip collector for clean work
- No need of lubrication
- Maximum cutting depth 3,22" / 2,20 bevel cut and thickness 0,40"

CHIP COLLECTOR



Ideal for gratings with LBS saw blade shock-resistant



Cuts sheet metal up to 10 mm and sandwich panels and profiles with a cutting depth of up to 82 mm



Depth adjustment with scaling



Chip compartment



45° bevel cut

| Power input | Voltage     | No load speed | Net weight    | Blade size  | Bore      | Cable length |
|-------------|-------------|---------------|---------------|-------------|-----------|--------------|
| 15 amps     | 115V / 60Hz | 2.600 rpm     | 16 lbs/7,1 kg | Ø 9"/230 mm | Ø 1"/25,4 | 5 m          |

| Hand Dry Cutter 8230N + Case  |                                   | Reference                         |
|---|-----------------------------------|-----------------------------------|
| with Ø 9"/48T saw blade for stainless steel + 2 adapters for guide rail   |                                   | 608280IUS                         |
| with 9"/48T saw blade for stainless steel + adjustable cutting guide rail with integrated clamping system + 2 adapters for guide rail |                                   | 608280IUSET                       |
| Max. cutting capacities   |                                   |                                   |
|   | 90°                               | 45° (bevel cut)                   |
| Round   | 3,228" x 0,196"<br>82 x 6 mm      | 2,204" x 0,157"<br>56 x 6 mm      |
| Square  | 3,228" x 0,196"<br>82 x 82 x 6 mm | 2,204" x 0,157"<br>56 x 56 x 4 mm |
| Angle   | 3,228" x 0,393"<br>82 x 82 x 6 mm | 2,204" x 0,314"<br>56 x 56 x 4 mm |
| Plane   | 0,393"/10 mm                      | 0,314"/8 mm                       |
| Cutting depth   | 3,228"/82 mm                      | 2,204"/56 mm                      |

| Saw blades  | Reference   |
|---|-------------|
| Ø 9"/48T  | 72123048    |
| Ø 9"/48T steel and stainless steel                                | 72123048I   |
| Ø 9"/48T steel and stainless steel - coated food and construction | 72123048NSF |
| Ø 9"/60T - aluminum   | 72123060    |
| Ø 9"/68T- thin walled material                                    | 72123068    |
| Ø 9"/84T - thin sheets  | 72123084    |
| Ø 9"/60T - LBS metal grids  | 72223060    |

| Accessories  | Reference |
|--|-----------|
| Cutting guide rail with integrated clamping system (24" - 47" / 600 - 1200 mm) | 608284    |