



# PREMIUM SUPER DRY CUTTER 9435

## THE BESTSELLER

Metal saw by Jepson Power for fast and burr free cutting of metal pipes and profiles without coolant

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, stainless steel, aluminum, plastic and composite materials
- No need of lubricant and manual deburring
- Exclusive blade stabilising system reduces vibration
- High torque motor for continuous operation
- Patented quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Fitted with a Ø 14"/90T (355/90T) carbide tipped saw blade
- Optional stand for a comfortable and save work place
- CE approved operating system



**TWO PATENTED STABILIZERS FOR A BETTER CUTTING SURFACE AND LONG CUTTING LIFE**



**„K“ CLAMPING SET FOR SQUARE TUBES**  
 For a safer and more stable sawing process (included)



**QUICK RELEASE QUICK RELEASE SYSTEM**  
 Enables precise and efficient clamping



**RIP FENCE**  
 Increased stability - makes it easier to saw short materials



**MITER CUTS CAN BE ADJUSTED WITHOUT TOOLS**  
 from 90-75-60-45°



**CHIP COLLECTOR**  
 For a clean workplace

| Power input | Voltage   | No load speed | Net weight  | Blade size    | Bore      |
|-------------|-----------|---------------|-------------|---------------|-----------|
| 21 amps     | 115V/50Hz | 1.400 rpm     | 56 lbs/25kg | Ø 14" /355 mm | Ø 1"/25,4 |

| Premium Super Dry Cutter 9435 | Reference  |
|-------------------------------|------------|
| with 14"/355 mm/90T saw blade | 600560UST3 |

| Max. cutting capacities | 90°            |                               | 45°            |                              |
|-------------------------|----------------|-------------------------------|----------------|------------------------------|
|                         | Round          | Square                        | Rectangular    |                              |
|                         | 5,511" /140 mm | 4,921" x 4,921" /125 x 125 mm | 4,724" /102 mm | 3,149" x 3,149" /80 x 80 mm  |
|                         |                | 4,133" x 6,102" /105 x 155 mm |                | 2,952" x 3,937" /75 x 100 mm |

| Saw blades   | Reference |
|--|-----------|
| Ø 14"/90T for steel and stainless steel - coated food and construction | 600570NSF |
| Ø 14"/120T steel and stainless steel - extra thin                      | 600512I   |
| Ø 14"/90T steel and stainless steel - thin                             | 600570S   |
| Ø 14"/72T steel and stainless steel - medium                           | 600580S   |
| Ø 14"/60T steel and stainless steel - thick                            | 600590    |
| Ø 14"/60T - cast iron  | 600591S   |
| Ø 14"/66T - mild steel   | 600595S   |
| Ø 14"/96T - aluminum   | 600594    |
| Accessories  | Reference |
| Stand for PSDC 9435  | 600526T3  |
| Eccentric clamping system  | 609910    |
| Thinfix - Clamping system for open profiles                            | 600546    |