

HAND DRY CUTTER 8230N

THE AGILE

- Ideal for cutting sheet metal, sandwich panels, pipes and steel profiles, non-ferrous materials and composites
- Strong and light construction, only 16 lbs (7,1 kg)
- Chip collector for clean work
- No need for lubrication thanks to our dry cut technology
- Max. cutting depth 90°: 3 3/4" (82 mm) | 45°: 2 3/8" (56 mm) and max. wall-thickness .40" (10 mm)

Included:
 Ø 8" (230 mm) 48T CT saw blade for stainless steel



CHIP COLLECTOR




Ideal for gratings with LBS saw blade shock-resistant



Cuts sheet metal up to 3/8" (10 mm) and sandwich panels and profiles with a cutting depth of up to 3 3/4" (82 mm)



Depth adjustment with scaling



Chip compartment



45° bevel cut

| Power input | Voltage | No load speed | Net weight | Blade size | Bore | Cable length |
|-------------|-------------|---------------|-----------------|---------------|----------------|-----------------|
| 15 amps | 115V / 60Hz | 2.600 rpm | 16 lbs (7,1 kg) | Ø 9" (230 mm) | Ø 1" (25,4 mm) | 16 1/2 ft (5 m) |

| Hand Dry Cutter 8230N + Case | Reference |
|---|-----------|
| with Ø 9" (230 mm) 48T saw blade for stainless steel - 115V | 608280IUS |
| with Ø 9" (230 mm) 48T saw blade for stainless steel - 230V | 608280I |

| | Max. cutting capacities | |
|----------------------|----------------------------------|---------------------------------|
| | 90° | 45° (bevel cut) |
| Round | 3 1/4" x 3/16" 82 x 6 mm | 2 3/8" x 1/8" 56 x 4 mm |
| Square | 3 1/4" x 3/16" 82 x 82 x 6 mm | 2 3/8" x 1/8" 56 x 56 x 4 mm |
| Angle | 3 1/4" x 3/16" 82 x 82 x 6 mm | 2 3/8" x 1/8" 56 x 56 x 4 mm |
| Plane | 3/8" / 10 mm | 5/16" / 8 mm |
| Cutting depth | 3 3/4" / 82 mm | 2 3/8" / 56 mm |









ECO-FRIENDLY
 Dry Cutting-Technology



ACCESSORIES (OPTIONAL)

Selecting the correct number of teeth depends on the wall/diameter of the material. We will be happy to advise you. (201)-916-4709

| Carbide tipped saw blades | Ø | | Teeth | Bore | | Kerf | | Max. Speed | Reference |
|--|-----|------|-------|------|------|------|------|-------------------------|---|
| | mm | inch | | mm | inch | mm | inch | | |
| Steel | 230 | 9 | 48 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123048  |
| Stainless steel & steel | 230 | 9 | 48 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123048I  |
| Stainless steel NSF coated | 230 | 9 | 48 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123048NSF  |
| Aluminum | 230 | 9 | 60 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123060  |
| Steel (thin-walled) | 230 | 9 | 68 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123068  |
| Steel (extra thin-wall) | 230 | 9 | 84 | 25,4 | 1 | 2,0 | .079 | 3.000 min ⁻¹ | 72123084  |
| Steel (thin-walled) "LBS - impact resistant" | 230 | 9 | 60 | 25,4 | 1 | 1,4 | .055 | 3.000 min ⁻¹ | 72223060  |



Cutting guide rail with integrated clamping system

Length 2ft - 4ft / 600 - 1200 mm
 Ref. 608284




Guide rail SET

Length 4 ft 7" 1.400 mm
 Incl. 2 quick release clamps
 Incl. 2 adapters (608275A)
 Ref. 608275ASET



Set of 2 adapters for guide rail 4ft 7"

Ref. 608275A



Connector for guide rail

Ref. 608275B



Quick release clamp for guide rail (2 pcs.)

Ref. 6082755