

Super Hand Dry Cutter 8320 - BIG²

- **Super Hand Dry Cutter 8320 with Ø 12 5/8"/84T HM saw blade:**
- Ideal for cutting **sandwich panels**, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to **cutting depth of 4 3/4" on guide rail**
- **Dry cutting without lubricant, instead of a chainsaw**
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:
green: ok | orange: warning | red: over load
- **Lightweight magnesium: 8,4 lbs**



Cutting guide 4ft 7" with quick fixation

- Ideal for clean and straight cutting of sandwich panels
- Delivered with 2 C-clamps

Specifications	
Power input	15 amps
Voltage	115V/60Hz
No load speed	1.700 rpm
Net weight	8,4 lbs
Blade size	12 5/8"
Cable	16 ft 5"

Saw Blades	Ref.
Cutting guide rail 4ft 7"	608275D
Ø 12 5/8" HM Saw blade	608276
Ø 12 5/8" HM Saw blade for stainless steel - food & construction	608276NSF

Super Hand Dry Cutter	Ref.
Super Hand Dry Cutter 8320 - delivered with Ø 12 5/8"/84T Saw blade	608270 / 608270 U